

HUB



Designation	Principal Dimensions(mm)			Basic Load Ratings(KN)		Limited Speed(rpm)		Weight
	d	D	T	Dynamic(Cr)	Static(Cor)	Grease	Oil	(kg)
81105	25	42	11	33.5	76	3200	6300	0.053
81105M	25	42	11	33.5	76	3200	6300	0.053
81106	30	47	11	35.5	86	3000	6000	0.057
81106M	30	47	11	35.5	86	3000	6000	0.057
81206	30	52	16	64	141	2400	4800	0.12
81206M	30	52	16	64	141	2400	4800	0.12
81107	35	52	12	29	93	2800	5600	0.073
81107M	35	52	12	29	93	2800	5600	0.073
81207	35	62	18	62	190	2000	4000	0.21
81207M	35	62	18	62	190	2000	4000	0.21
81108	40	60	13	43	137	2400	5000	0.11
81108M	40	60	13	43	137	2400	5000	0.11
81208	40	68	19	83	255	1900	3800	0.25
81208M	40	68	19	83	255	1900	3800	0.25
81109	45	65	14	45	153	2200	4500	0.13
81109M	45	65	14	45	153	2200	4500	0.13
81209	45	73	20	83	255	1800	3600	0.29
81209M	45	73	20	83	255	1800	3600	0.29

Thrust roller 80000 series

81110	50	70	14	47.5	166	2200	4300	0.14
81110M	50	70	14	47.5	166	2200	4300	0.14
81210	50	78	22	91.5	300	1700	3400	0.36
81210M	50	78	22	91.5	300	1700	3400	0.36
81111	55	78	16	69.5	285	1900	3800	0.23
81111M	55	78	16	69.5	285	1900	3800	0.23
81211	55	90	25	122	390	1400	2800	0.57
81211M	55	90	25	122	390	1400	2800	0.57
81112	60	85	17	80	300	1800	3600	0.27
81112M	60	85	17	80	300	1800	3600	0.27
81212	60	95	26	137	465	1400	2800	0.65
81212M	60	95	26	137	465	1400	2800	0.65