


HUB



Bearing Number	Dimensions			Chamfer(min)	Basic Load Rating		Limiting Speed (X1000 RPM)		Weight(Kg)
	d	D	B	(rs)	Cr(N)	Cor(N)	Grease	Oil	
6000	10mm	26mm	8mm	0.3	4550	1950	31	36	19
6000 2RS	10mm	26mm	8mm	0.3	4550	1950	31	36	19
6000zz	10mm	26mm	8mm	0.3	4550	1950	31	36	19
6200	10mm	30mm	9mm	0.6	5100	2400	24	29	32
6200 2RS	10mm	30mm	9mm	0.6	5100	2400	24	29	32
6200zz	10mm	30mm	9mm	0.6	5100	2400	24	29	32
6300	10mm	35mm	11mm	0.6	8100	3450	22	27	53
6300 2RS	10mm	35mm	11mm	0.6	8100	3450	22	27	53
6300zz	10mm	35mm	11mm	0.6	8100	3450	22	27	53
6001	12mm	28mm	8mm	0.3	5100	2400	27	32	22
6001 2RS	12mm	28mm	8mm	0.3	5100	2400	27	32	22
6001zz	12mm	28mm	8mm	0.3	5100	2400	27	32	22
6201	12mm	32mm	10mm	0.6	6800	3050	22	27	37
6201 2RS	12mm	32mm	10mm	0.6	6800	3050	22	27	37
6201zz	12mm	32mm	10mm	0.6	6800	3050	22	27	37
6301	12mm	37mm	12mm	1	9700	4200	20	25	60

Metric Deep Groove Ball Bearings

6301 2RS	12mm	37mm	12mm	1	9700	4200	20	25	60
6301zz	12mm	37mm	12mm	1	9700	4200	20	25	60
6002	15mm	32mm	9mm	0.3	5600	2850	23	27	30
6002 2RS	15mm	32mm	9mm	0.3	5600	2850	23	27	30
6002zz	15mm	32mm	9mm	0.3	8100	3450	23	27	30
6202	15mm	35mm	11mm	0.6	7650	3750	20	24	45
6202 2RS	15mm	35mm	11mm	0.6	7650	3750	20	24	45
6202zz	15mm	35mm	11mm	0.6	7650	3750	20	24	45
6302	15mm	42mm	13mm	1	11400	5450	17	20	82
6302 2RS	15mm	42mm	13mm	1	11400	5450	17	20	82
6302zz	15mm	42mm	13mm	1	11400	5450	17	20	82
6003	17mm	35mm	10mm	0.3	6000	3250	21	25	39
6003 2RS	17mm	35mm	10mm	0.3	6000	3250	21	25	39
6003zz	17mm	35mm	10mm	0.3	6000	3250	21	25	39