


HUB



Bearing Number	Dimensions			Basic Load Rating		Limiting Speed (X1000 RPM)		Number Of Ball	Ball Diameter	Weight(Kg)
	d	D	B	Cr(N)	Cor(N)	Grease	Oil			
RW0	1.191mm	3.967mm	1.588mm	21	6	110	130	7	0.599	0.15
RW0zz	1.191mm	3.967mm	2.38mm	21	6	110	130	7	0.599	0.15
RW1	1.397mm	4.762mm	1.984mm	44	12	90	110	6	1	0.19
RW1zz	1.397mm	4.762mm	2.779mm	44	12	90	110	6	1	0.19
RW1-4	1.984mm	6.35mm	2.38mm	54	17	67	80	7	1	0.53
RW1-4zz	1.984mm	6.35mm	3.571mm	54	17	67	80	7	1	0.53
RW133	2.38mm	4.762mm	1.588mm	28	10	80	95	10	0.599	0.15
RW133zz	2.38mm	4.762mm	2.38mm	28	10	80	95	10	0.599	0.15
RW1-5	2.38mm	7.938mm	2.779mm	106	32	60	71	6	1.588	1.15
RW1-5zz	2.38mm	7.938mm	3.571mm	106	32	60	71	6	1.588	1.15
RW144	3.175mm	6.35mm	2.38mm	54	17	67	80	7	1	0.4
RW144zz	3.175mm	6.35mm	2.779mm	54	17	67	80	7	1	0.4
RW2-5	3.175mm	7.938mm	3.779mm	107	32	60	67	6	1.588	0.74
RW2-5zz	3.175mm	7.938mm	3.571mm	107	32	60	67	6	1.588	0.74
RW2-6	3.175mm	9.525mm	2.779mm	122	41	53	63	7	1.588	1.23
RW2-6zz	3.175mm	9.525mm	3.571mm	122	41	53	63	7	1.588	1.23
RW2	3.175mm	9.525mm	3.967mm	121	39	56	67	7	1.588	1.37
RW2zz	3.175mm	9.525mm	3.967mm	121	39	56	67	7	1.588	1.37
RW155	3.967mm	7.938mm	2.779mm	69	27	53	63	10	1	0.61
RW155zz	3.967mm	7.938mm	3.175mm	69	27	53	63	10	1	0.61
RW156	4.763mm	7.938mm	2.779mm	69	27	53	63	10	1	0.45
RW156zz	4.763mm	7.938mm	3.175mm	69	27	53	63	10	1	0.45

Miniature Bearings With Extended Inner Rings

RW166	4.763mm	9.525mm	3.175mm	136	49	50	60	8	1.588	0.85
RW166zz	4.763mm	9.525mm	3.175mm	136	49	50	60	8	1.588	0.85
RW3	4.762mm	12.7mm	3.967mm	249	88	43	53	7	2.38	2.95
RW3zz	4.762mm	12.7mm	4.978mm	249	88	43	53	7	2.38	2.95
RW168	6.35mm	9.525mm	3.175mm	71	31	48	56	11	1	0.6
RW168zz	6.35mm	9.525mm	3.175mm	71	31	48	56	11	1	0.6
RW188	6.35mm	12.7mm	3.175mm	207	80	40	50	8	1.999	2.32
RW188zz	6.35mm	12.7mm	4.762mm	207	80	40	50	8	1.999	2.32