


HUB



Bearing NO.	Boundary dimensions(mm)			Limiting speed(rpm)		Basic load ratings(kN)		Mass (kg)
	d	D	B	Grease	Oil	Cr	Cor	Refer
N211E	55	100	21	5300	6700	80.2	95.5	0.62
N210E	50	90	20	6000	7500	61.2	69.2	0.56
N209E	45	85	19	6300	8000	58.5	63.8	0.52
N208E	40	80	18	7000	9000	51.5	53	0.39
N207E	35	72	17	7500	9500	46.5	48	0.344
N206E	30	62	16	8500	11000	36	35.6	0.22
N205E	25	52	15	11000	14000	27.5	26.8	0.148
N204E	20	47	14	17000	20000	16.6	13.9	0.109
N203E	17	40	12	18000	18000	17.6	14.6	0.009
N202E	15	35	11	20000	22000	12.7	10.4	0.148
NU238EM	190	340	55	1600	1900	695	955	24
N236EM	180	320	52	1700	2000	25	850	20
N234EM	170	310	52	1800	2200	605	800	19.2
N232EM	160	290	48	1900	2200	500	665	15.5
N230E	150	270	45	2000	2400	450	595	12.5
N228E	140	250	42	1800	2400	302	415	9.01
N226E	130	230	40	2000	2800	358	372	7.38
N224E	120	215	40	2200	3000	247	249	6.32
N222E	110	200	38	2600	3400	239	342	5.11

Cylindrical roller bearing FC FCD series Bearing manufacturer

N221E	105	190	36	2800	3600	224	238	4
N220E	100	180	34	3000	3800	208	226	3.14
N219E	95	170	32	3200	4000	192	214	2.8
N218E	90	160	30	3400	4300	170	203	2.5
N217E	85	150	28	3600	4500	158	192	2.08
N216E	80	140	26	3800	4800	132	165	1.74
N215E	75	130	25	4000	5000	125	155	1.45
N214E	70	125	24	4300	5300	112	135	1.29
N213E	65	65	23	4500	5600	102	118	1.05
N212E	60	110	22	5000	6300	89.8	102	0.84
N240EM	200	360	58	1500	1800	765	1060	28.6