


HUB



Designation		Principal dimensions (mm)			Basic load ratings (kN)		Limiting Speed		Weight (kg)
Cylindrical Bore	Taper Bore	d	D	B	Dyn Cr	Stc Cor	Speed Ratings	Limiting Speed	
30202	7202E	15	35	11	14.9	13.4	12000	16000	0.053
30203	7203E	17	40	12	20.8	21.8	9000	12000	0.079
30204	7204E	20	47	14	28.2	30.5	8000	10000	0.126
30205	7205E	25	52	15	32.2	37	7000	9000	0.154
30206	7206E	30	62	17.5	43.2	50.5	6000	7500	0.231
30207	7207E	35	72	17	54.2	63.5	5300	6700	0.331
30208	7208E	40	80	18	63	74	5000	6300	0.422
30209	7209E	45	85	19	67.8	83.5	4500	5600	0.474
30210	7210E	50	90	20	73.2	92	4300	5300	0.529
30211	7211E	55	100	21	90.8	115	3800	4800	0.713
30212	7212E	60	110	22	102	130	3600	4500	0.904
30213	7213E	65	120	23	120	152	3200	4000	1.13
30214	7214E	70	125	24	132	175	3000	3800	1.26
30215	7215E	75	130	25	138	185	2800	3600	1.36
30216	7216E	80	140	26	160	212	2600	3400	1.67
30217	7217E	85	150	31	178	238	2400	3200	2.06
30218	7218E	90	160	30	200	270	2200	3000	2.54

Single Row Tapered Roller Bearings

30219	7219E	95	170	32	228	308	2000	2800	3.04
30220	7220E	100	180	34	255	350	1900	2600	3.72
30222	7222E	110	200	38	315	445	1700	2200	5.21
30224	7224E	120	215	40	338	482	1500	1900	6.2
30226	7226E	130	230	40	365	520	1400	1800	6.94
30228	7228E	140	250	42	408	585	1200	1600	8.73
30230	7230E	150	270	45	450	645	1100	1500	10.8
30232	7232E	160	290	48	512	738	1000	1400	13.3
30234	7234E	170	310	52	590	865	1000	1300	16.6
30238	7238E	190	340	55	698	1030	850	1100	20.8
30240	7240E	200	360	58	685	972	940	1200	25.6
30302	7302E	15	42	13	22.8	21.5	9000	12000	0.094
30303	7303E	17	47	14	28.2	27.2	8500	11000	0.129